

drapilux	911	—	PES-FR	B1	IMO 01	60m	abt. 20.000	grade 4						D	C	ca. 245 g/m ²	print on basic quality-243	individual print	100 % PES	150	X	—	O	—
drapilux	911	—	PES-FR	B1	IMO 01	40m	abt. 20.000	grade 4						D	C	ca. 245 g/m ²	print on basic quality-243	individual print	100 % PES	310	X	—	O	—
drapilux	917	—	Trevira CS	B1	IMO 01	60m	abt. 80.000	grade 4						C	B	ca. 405 g/m ²	print on basic quality-239	individual print	100 % PES	145	X	—	O	—
drapilux	918	—	Trevira CS	B1	IMO 02	40m	—	—						—	—	ca. 95 g/m ²	print on basic quality-808	individual print	100 % PES	290	X	—	O	—
drapilux	921	—	Trevira CS	B1	IMO 02	40m	abt. 25.000	grade 4						D	C	ca. 220 g/m ²	print on basic quality-112	individual print	100 % PES	300	X	O	O	O
drapilux	922	—	Trevira CS	B1	IMO 02	40m	—	—						—	—	ca. 75 g/m ²	print on basic quality-750	individual print	100 % PES	310	X	O	O	O

B1 = flammstop permanent flame retardant acc. to DIN 4102 B1

making up 01 = not folded

making up 02 = folded

= permanently flame-retardant acc. intern. standards

= drapilux bioaktiv

= suitable as upholstery (DIN EN 14465)

= suitable as bedspread, high pilling resistance

= suitable as side panels

= Dim-out fabric (DIN EN 14501)

= Black-Out fabric (DIN EN 14501)

= discontinued item; subject to prior sale

article marked with *

added values - different options	
(X)	= standard finish
(O)	= special finish on request

aW-values	
0,90; 0,95; 1,00	
0,80; 0,85	
0,60; 0,65; 0,70; 0,75	
0,30; 0,35; 0,40; 0,45; 0,50; 0,55	
0,25; 0,20; 0,15	
0,10; 0,05; 0,00	